

Data Sheet

FAST TACK HT

High tack sealant tape for 427°C applications

DESCRIPTION

New generation sealant tape for high temperature applications. Fast Tack HT builds tack quickly when applied to Thermalimide. Having good room temperature adhesion to the high temp bagging film reduces the time required to vacuum bag high temperature parts.

BENEFITS

- Easiest to use high temperature tape.
- Adheres well to polyimide films.
- Improved high temperature performance vs legacy products.

TECHNICAL DATA

Colour	Sky blue
Base material	Silicone
Maximum use temperature	427°C
Shelf life	12 months from date of manufacture
Storage conditions	Tape must be stored flat in original packaging at 22°C Do not refrigerate

SIZES

Dimensions	Packaging	Remarks
(3 mm x 12 mm x 7,5 m) (1/8 inch x 1/2 inch x 25 feet)	40 rolls per case	Can be sold per unit roll



NOTES

- After applying the bag to the sealant tape, allow it to sit approximately 30 minutes for best adhesion results.
- For clean removal, it is recommended to strip the tape from the mold surface once it has cooled down to room temperature.
- The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, Airtech recommends testing prior to use.
- Cotton gloves are recommended when using product. Change gloves immediately after handling product.

Last updated : 2018-10-04

Catalogue position : [Vacuum bag sealant tapes](#)