ZI Haneboesch L-4562 Differdange I UXFMBOURG Phone: +352 58 22 82 1 Fax: +352 58 49 35 E-mail: sales@airtech.lu Website: www.airtech.lu

## **Data Sheet**

**GS-333LT** 

# Vacuum bag sealant tape for longer cures

### DESCRIPTION

GS-333LT is a low tack version of our standard GS-333 tape. GS-333LT is a sealant tape which has been designed to take longer cures and still remove cleanly. It is usable up to 204°C.

#### BENEFITS

- Designed to last longer to make lengthy cure cycles safer.
- Removes cleanly after cure reducing the cost of tool cleaning.
- Multi-purpose tape can be used on metal and composite tooling.

#### TECHNICAL DATA

Colour Black

Base material Synthetic rubber

Maximum use temperature 204°C

Shelf life 12 months from date of manufacture

Storage conditions

Tape must be stored flat in original packaging at 22°C

Do not refrigerate

## SIZES

Dimensions	Packaging
3 mm x 12 mm x 7,5 m (1/8 inch x 1/2 inch x 25 feet)	40 rolls per case
THE RESERVE OF THE PARTY OF THE	

## NOTES

- For clean removal, it is recommended to strip the tape from the mould surface once it has cooled down to room temperature.
- The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, Airtech recommends testing prior to use.

Last updated: 2018-09-11